

X

EDC-150S105ST-000x

Rev. B

= /6 5 W« —

Î´ì ×

¿ d	£ 3 š	À¹ š	£ Ü š	Ô I
ÿ µ 9 8	140 Vac	-	305 Vac	
ÿ µ È ä 8	47 Hz	-	63 Hz	
¥ v	-	-	0.70 mA	IEC60598-1; 240Vac/60Hz
ÿ µ v	-	-	1.0 A	¿ ú k < G I
~ ... v / Z	-	-	0.54 A²s	< G I k q) ê “ g Ò Ñ o h k / V Q / V Q k 4 Ò ž • # f Y z Õ Ñ @ f ~ ... v ¼ ¿
ä œ f	0.90	-	-	200-277Vac, 50-60Hz, 75%-100% ¿ ú
È´ f â 1	-	-	20%	(112.5~150W)
È´ f â 1	-	-	10%	220-240Vac, 50-60Hz, 75%-100% ¿ ú (112.5~150W)

Î ¢4ì ×

¿ d	£ 3 š	À¹ š	£ Ü š	Ô I
ÿ ß v ¢ †	-8%lo	-	8%lo	¿ ú
o Ĩ v	-	-	10%lomax	¿ ú
q ú ÿ ß 9 EDC-150S105ST-0007 EDC-150S105ST-0004 EDC-150S105ST	- - -	- - -	250 V 250 V 250 V	
¿ Å² ... ä	-	-	± 5.0%	¿ ú
¿ Ú² ... ä	-	-	± 5.0%	
• Ñ • ž •	-	-	0.5 s	220Vac, 75%-100% ¿ ú .
“ † © f	-	0.04%/ ¢	-	Ó “ = 0 ¢ ~Tc Â Ý >

P á é

¿ d	£ 3 š	À¹ š	£ Ü š	Ô I
ä @220Vac: EDC-150S105ST-0007 EDC-150S105ST-0004 EDC-150S105ST	90.0% 90.0% 89.0%	92.0% 92.0% 91.0%	- - -	¿ ú k - ê “ z Ò Ñ ž k ä ‘ z³
u ® — { ž ž •	-	616,000 Hours	-	< G I k ê “ - k ¿ ú 3 / 2 . * (1
. x ž •	-	97,000 Hours	-	< G I k ¿ ú k q) Ó “ k Õ Ñ @ f . x ¼ ¿

62 ;

58°F

EDC-150S105ST-0007(I_o=700mA)

82 ;

58°F



; 2 ;

58°F