



EDC-150S105SV-000x

Rev.D

EDC-150S105SV-000x 150W IP66/IP

(mA)	(Vdc)	(W)
700	107-214	150
860	97-174	150
1050	97-143	150

- 1


220 Vac 100%
- 2

: 220-240Vac
- 3

100-305Vac 100%
- 4

BIS

Io/Iomax





	140 Vac	-	305 Vac	
	47 Hz	-	63 Hz	
	-	-	0.70 mA	IEC 60598-1; 240Vac/60Hz
	-	-	0.83 A	100% 220Vac
(I ² t)	-	-	0.019 A ² s	220Vac 25 C

(L × W × H) (L × W × H)	6.54 × 2.36 × 1.44 166 × 60 × 36.5			7.20 × 2.36 × 1.44 183 × 60 × 36.5
	-	680 g	-	

CE	EN 61347-1, EN 61347-2-13
BIS	IS 15885(PART2/SEC13)
KS	KS C 7655
EMI	
EN IEC 55015 ⁽¹⁾	Conducted emission Test & Radiated emission Test
EN IEC 61000-3-2	Harmonic current emissions
EN 61000-3-3	Voltage fluctuations & flicker
EMS	
EN 61000-4-2	Electrostatic Discharge (ESD): 8 kV air discharge, 4 kV contact discharge
EN 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test-RS
EN 61000-4-4	Electrical Fast Transient / Burst-EFT
EN 61000-4-5	Surge Immunity Test: AC Power Line: Differential Mode 4 kV, Common Mode 6 kV
EN 61000-4-6	Conducted Radio Frequency Disturbances Test-CS
EN 61000-4-8	Power Frequency Magnetic Field Test
EN 61000-4-11	Voltage Dips
EN 61547	Electromagnetic Immunity Requirements Applies To Lighting Equipment

1 EMI (



EDC-150S105SV-000x

Rev.D

150W IP66/IP67

EDC-150S105SV-0007(Io=700mA)



EDC-150S105SV-000x

Rev.D

150W IP66/IP67

--	--	--	--	--

My 6Eet(IfhWBQF(ybEf(E"AS&hRdB)RvfqTEj

EDC-150S105SV-000x

Rev.D

150W IP66/IP67



2017-03-03	A	➤	/	/
			/	

2021-01-05 B